







Tragfähigkeiten für Anschlagpunkte, Schweißbausführung

			TWN 0119 Anschlagpunkt								TWN 0124 Anschlagpunkt mit Feder							
Einsatzart	Neigungswinkel β	Strangzahl																
			Angabe der Tragfähigkeiten in [t max.]															
	Kennzeichnung		1,12	2	3,15	5,3	8	15	31,5	50			1,12	2	3,15	5,3		
	0°	1	1,12	2	3,15	5,3	8	15	31,5	50			1,12	2	3,15	5,3		
	0°	2	2,24	4	6,3	10,6	16	30	63	100			2,24	4	6,3	10,6		
	90°	1	1,12	2	3,15	5,3	8	15	31,5	50			1,12	2	3,15	5,3		
	90°	2	2,24	4	6,3	10,6	16	30	63	100			2,24	4	6,3	10,6		
	0-45°	2	1,6	2,8	4,25	7,5	11,2	21,2	45	71			1,6	2,8	4,25	7,5		
	45-60°	2	1,12	2	3,15	5,3	8	15	31,5	50			1,12	2	3,15	5,3		
	unsymmet.	2	1,12	2	3,15	5,3	8	15	31,5	50			1,12	2	3,15	5,3		
	0-45°	3+4	2,36	4,25	6,7	11,2	17	31,5	67	106			2,36	4,25	6,7	11,2		
	45-60°	3+4	1,7	3	4,75	8	11,8	22,4	47,5	75			1,7	3	4,75	8		
	unsymmet.	3+4	1,12	2	3,15	5,3	8	15	31,5	50			1,12	2	3,15	5,3		