

Druckverluste in Sanipex MT Systemteilen (Wasser 10°C)



Art. Nr.	Bezeichnung	Symbol	DN/d	ζ-Wert (bei w = 2m/s)	Gleichwertige (äquivalente) Rohrlängen in Meter														
					1 BW 0.1 U/s	2 BW 0.2 U/s	3 BW 0.3 U/s	4 BW 0.4 U/s	8 BW 0.5 U/s	30 BW 0.8 U/s	60 BW 1.0 U/s	1.0 U/s	1.5 U/s	2.0 U/s	2.5 U/s	3.0 U/s	3.5 U/s	4.0 U/s	
4630 4632	Sanipex MT Dose einfach 90°		1/2"-d16	1.3	0.45	0.50	0.55	0.60	-	-	-	-	-	-	-	-	-	-	
				1.3	0.55	0.65	0.75	0.80	0.85	-	-	-	-	-	-	-	-	-	-
				1.6	0.65	0.80	0.85	0.95	1.00	-	-	-	-	-	-	-	-	-	-
4634	Sanipex MT Dose 2-fach 90°		1/2"-d16-d16	4.0	1.40	1.65	1.85	2.00	-	-	-	-	-	-	-	-	-	-	
				3.2	1.10	1.35	1.50	1.60	1.70	-	-	-	-	-	-	-	-	-	
				1.5	0.55	0.65	0.70	0.75	-	-	-	-	-	-	-	-	-	-	-
4610	Armatureanschluss einfach		1/2"-d20-d16	0.7	0.25	0.30	0.30	0.35	0.35	-	-	-	-	-	-	-	-	-	
				3.0	1.05	1.25	1.35	1.45	-	-	-	-	-	-	-	-	-	-	
				3.3	1.40	1.65	1.80	1.95	2.10	-	-	-	-	-	-	-	-	-	
				2.1	0.90	1.05	1.15	1.25	1.30	-	-	-	-	-	-	-	-	-	
4611	Armatureanschluss doppelt		1/2"-d16-d16-50 mm	2.7	1.00	1.10	1.25	1.35	-	-	-	-	-	-	-	-	-	-	
				2.1	0.75	0.85	0.95	1.05	-	-	-	-	-	-	-	-	-	-	
				1.0	0.35	0.40	0.45	0.50	-	-	-	-	-	-	-	-	-	-	
4640 4645	Verteiler inkl. Übergang		3/4"-d20	0.8	0.35	0.40	0.45	0.50	-	-	-	-	-	-	-	-	-	-	
				0.5	-	-	0.35	0.35	0.40	0.45	-	-	-	-	-	-	-	-	
				2.1	0.75	0.85	0.95	1.05	-	-	-	-	-	-	-	-	-	-	
4670 4671 4672	Winkel 90°		d16	1.9	0.85	1.00	1.10	1.15	1.25	-	-	-	-	-	-	-	-	-	
				1.8	-	-	-	1.35	1.45	1.60	-	-	-	-	-	-	-		
				1.7	-	-	-	-	-	1.85	1.95	2.15	2.30	-	-	-	-		
				1.6	-	-	-	-	-	2.10	2.20	2.45	2.65	2.80	-	-			
				0.8	-	-	-	-	-	-	-	1.55	1.70	1.80	1.90	-			
				0.9	-	-	-	-	-	-	-	-	2.25	2.40	2.50	2.60	2.70		
4676	Winkel 45°		d20	0.7	0.30	0.35	0.40	0.45	0.45	-	-	-	-	-	-	-	-	-	
				0.6	-	-	-	0.45	0.50	0.55	-	-	-	-	-	-			
				0.6	-	-	-	-	-	0.60	0.65	0.75	0.80	-	-	-			
				0.6	-	-	-	-	-	0.75	0.80	0.85	0.95	1.00	-	-			
				0.4	-	-	-	-	-	-	-	0.85	0.90	0.95	1.00	-			
				0.5	-	-	-	-	-	-	-	-	1.15	1.20	1.25	1.30	1.35		

