

Steckschlüssel 1/2 Zoll

190/1 6p



Profile








Standards





ISO 2725-1

Produkteigenschaften

- Material: Premium Flex Chrom-Vanadium-Stahl
- gesenkgeschmiedet, vollkommen gehärtet und vergütet
- verchromt gemäß EN12540
- poliert
- gefertigt gemäß ISO 2725-1 (nur metrische Dimension)
- gefertigt gemäß DIN 3124



		L	D1	D2	T↑		
605307	8	38	13.2	22.9	12	55	
610155	9	38	13.9	22.9	12	55	
600851	10	38	15	22.9	12	45	
600852	11	38	16.3	22.9	12	49	
600853	12	38	17.9	22.9	12	49	
600854	13	38	18.8	22.9	12	50	
600855	14	38	19.7	22.9	12	53	
600856	15	38	20.4	22.9	12	58	
600857	16	38	22.9	21.5	12	57	
600858	17	38	24.3	22	12	62	
600859	18	38	25.5	23	12	70	
600860	19	38	26.8	24	14	63	
600861	20	38	28.1	24	14	76	
600862	21	38	29.3	25	14	95	
600863	22	38	30.4	25	14	95	
600864	23	40	31.7	26	14	114	
600865	24	42	33.1	28	16	165	
600866	25	42	34.2	29	16	126	
600868	27	43	37	30	18	150	
600869	28	43	38	31	20	177	
600871	30	46	40.7	34	22	210	
600872	32	46	43.2	36	22	222	
610106	3/8"	38	15	22.9	12	55	
610108	1/2"	38	18.8	22.9	12	65	
610109	9/16"	38	20.4	22.9	12	65	
610111	11/16"	38	25.5	23	12	95	

		L	D1	D2	T↑		
610112	3/4"	38	26.8	24	14	105	
610116	1"	42	35.3	30	16	126	
610117	1.1/16"	43	37	30	18	180	
610118	1.1/8"	43	39	32	20	185	
610119	1.3/16"	46	40.7	34	22	237	
610120	1.1/4"	46	43.2	36	22	55	

* Bilder von Produkten sind Symbolfotos. Abmessungen sind in mm, Gewichte in Gramm.

Häufig gestellte Fragen

I attached the socket wrench to the pneumatic tool and the wall cracked. What could be wrong?

When working with pneumatic screwdrivers, you must use an impact socket wrench.